

# RELEASE NOTES

## RELEASE NOTICE

This is the May 2026 release notice for **Oceaneering® C-NAVX3** GNSS receiver firmware version 1.14.32.

## REVISION HISTORY

Revision	Release Date	Change Details	Author
D	13 - May - 2026	v1.14.33 firmware release	Ben Dean
C	10 - Oct - 2025	v1.13.15 firmware release	Ben Dean
B	17 - Mar - 2025	v1.10.37 firmware release	Ben Dean
A	03 - Mar - 2025	v1.10.34 firmware release	Ben Dean

## RELEASE AUTHORIZATION

Title	Signature	Date
Russel Morton	<i>Russell Morton</i>	13 - May - 2026

### Disclaimers:

C-NAV and C-Monitor are trademarks of Oceaneering International, Inc.

“This document is the property of Oceaneering International and may not be used for any purpose unless authorized in writing by Oceaneering and which, upon demand, shall be returned. For any queries, related to Warranty and Limitation of liability, please contact your Accounts Manager for more information.”

**TABLE OF CONTENTS**

1	OVERVIEW .....	3
2	REFERENCES .....	3
3	IMPORTANT NOTES .....	3
4	FIRMWARE CHANGES / IMPROVEMENTS .....	3
5	FIRMWARE ZIP FILE CONTENTS.....	4
6	SOFTWARE UPDATE APPLICATION.....	4
7	KNOWN ISSUES.....	4

## 1 OVERVIEW

This is the release notice for C-NAVX3® GNSS receiver firmware version 1.14.33.

This document describes the changes, improvements and the new features added since the previous formal release of version 1.13.15

## 2 REFERENCES



Document Number	Document Title
CNAV-MAN-0068	<a href="#">C-NAVX3 GNSS Receiver User Guide.</a>
CNAV-MAN-0066	<a href="#">C-NAVX3 Firmware Update Installation Procedure.</a>
CNAV-MAN-0063	<a href="#">C-NAVX1/C-NAVX3 RINEX Manual</a>
CNAV-BUL-0002	<a href="#">C-NAVX1 Age of Correction Data Bulletin.</a>

## 3 IMPORTANT NOTES

- This firmware will only function in C-NAVX3® GNSS receivers.
- Update the receiver with a consistent ensemble of firmware.
- Extract the ZIP file contents to a new folder to ensure that all the correct firmware and documentation are in one location and there is no mixing of old and new firmware.
- Always install the new firmware with the antenna connected and, in an area, where the receiver can track satellites.

## 4 FIRMWARE CHANGES / IMPROVEMENTS

- Added RTCMv3 RTK Rover Support. Serial or Ethernet message input only.
- Added C-NAV LEO Service Expiry Support. By using SBD the user can now see the C-NAV LEO service expiry date and number of days remaining.
- 1PPS default increased to 10ms.
- Added additional NMEA GGA Age of Correction (AoC) Scaling option. Users can now scale (reduce) the AoC by a factor of 10 or 60.
- User configuration preserved after firmware upgrade (e.g. baud rates, scheduled message outputs).
- Geoid choices that are not implemented have been removed from the drop-down menu in C-Controller.
- NMEA Force talker ID has been updated to include NMEA HDT sentence.

	<b>C-NAVX3 Firmware Release Notice</b> CNAV-RN-0007, Rev D	13 May 2026	
		Version 1.14.33	

## 5 FIRMWARE ZIP FILE CONTENTS

This C-NAVX3® GNSS receiver firmware is distributed in a compressed ZIP file. The ZIP file includes the following contents:

Filename	Version	Comments
1.14.33.itb	1.14.33	Zipped firmware image
CNAV-MAN-067 (C-NAVX3 Firmware Update Installation Procedure)	D	Firmware loading instructions
CNAV-RN-0007, Rev C (C-NAVX3 Firmware Release Notice)	D	This document
CNAV-MAN-063 (C-NAVX1/C-NAVX3 RINEX Procedure)	C	RINEX instructions
C-NAV Firmware Updater	1.6.1.5	Windows application for firmware loading

## 6 SOFTWARE UPDATE APPLICATION

This firmware has been tested and is intended to be used with the following versions of controller:

Software	Version	Tick off
C-Monitor QA/QC Software	10.4.0 and newer	<input checked="" type="checkbox"/>
C-NaviGator	10.4.0 and newer	<input checked="" type="checkbox"/>
C-Scape	10.4.0 and newer	<input checked="" type="checkbox"/>

Updates located internally on SharePoint C-NAV Software / Released Versions, in the corresponding software folders. At time of release externally on the public facing website.

## 7 KNOWN ISSUES

- Only one controller can be connected on COM ports and one on ETH ports simultaneously.
- VTG output copies the CMG (true) value to the CMG Magnetic value. The CMG magnetic should be a null field.
- Overloading any serial communications port (COM1 – COM4) >100% locks up I/O on all ports.
- C-NAV corrections over the internet first implementation doesn't have any status information to display.
- Receiver network settings are not retained during firmware updates.
- No NTRIP Client support. An NTRIP Client (for example BKG NTRIP Client) can be used to stream RTK data from the internet and send it out on a serial port to the C-NAVX3 Rover.